HIK134LE + Z25DV75 TWIN



professional bracket for mounting two cameras HIKVISION, DAHUA, TVT and other brands on a pipe or pole in a vertical or horizontal position



HIK134LE + Z25DV75 TWIN



HIK134LE + Z25DV75 TWIN + DS-1280ZJ-DM46 +DS-1260ZJ



bracket plate HIK134LE TWIN





technical parameters

material	AlMg3 thickness 3 mm
bracket (Fe galvanic zinc)	Z25DV75
weight	0,615kg
dimensions HIK134LE TWIN	120x130x123x3mm
openings	2xØ34, 4x oval 20x9, 16xØ3,5mm
installation	tube from Ø 27 up to Ø 62mm



UH85

use: the bracket has integrated mounting holes for sockets DS-1280ZJ-DM46, DS-1260ZJ, DS-1280ZJ-DM18, DS-1280ZJ-PT3J (Hikvision), TD-YXH0101B, TD-YXM0103 (TVT)

note: HIK134LE + Z25DV75 TWIN can also be used for other mounting bases (cameras), the preparation of the necessary mounting holes (Ø3.5mm) is not difficult as the HIK134LE TWIN plate is made of aluminum alloy (AlMg3)

Oval holes allow the use of other mounts in addition to the Z25DV75, e.g. Z85DV85, for jackel mounting it is possible to use UH85

supplied accessories: 8 pcs of self-tapping screws DIN7516 M4x12

